



INSTRUCTIONS FOR USE OF – 02 CBRN, OF-02 CBRN+ COMBINATION FILTERS

A2B2E2K2SXP3
TH3 A2B2E2K2SXP R SL
TM3 A2B2E2K2SXP R SL

GENERAL INFORMATION

The filter complies with requirements of the standards and regulations:

EN 14387:2021

Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing,

EN 12941:1998+A2:2008

Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood. Requirements, testing, marking.

EN 12942:1998+A2:2008

Respiratory protective devices. Power assisted filtering devices incorporating full face masks, half masks or quarter masks. Requirements, testing, marking.

EU 2016/425





Regulation of the European Parliament and of the Council on personal protective equipment.

MARKING

BASIC FILTER MARKING:

FILTER TYPE	CLASS	COLOUR MARKING	MAIN USE AGAINST
A	2	Brown	organic gases and vapours of organic substances with a boiling point > 65 °C
B	2	Grey	inorganic gases and vapours
E	2	Yellow	sulphur dioxide and other acid gases and vapours
K	2	Green	ammonia and organic amines
SX	-	Purple	phosgene
P	3	White	solid and liquid particles and aerosols, dust, bacteria and viruses

MEANING OF PICTOGRAMS:

	Read the instructions before use!		Filters not to be connected directly to a half mask		Maximum humidity for storage < 95%		Temperature range for storage -10°C to +50°C		End of shelf life year-month
---	-----------------------------------	---	---	---	------------------------------------	--	--	---	------------------------------

USE

The term „Combination filter“ means that it is an anti-gas filter that also contains a particulate filter. The filter is supplied with a thread connection Rd 40x1/7” (EN 148-1:2019, STANAG 2021) or with OZ 40x4 (GOST 8762-75).

The particulate filter part of the combination filter removes harmful solid and liquid particles, biologically solid and liquid aerosols, radioactive aerosols, dusts, bacteria and viruses from the passing air

THE OF-02 CBRN, OF-02 CBRN+ COMBINATION FILTERS

type A2B2E2K2SXP3 in combination with a suitable chemical protective mask or filter aid with auxiliary ventilation attached to a helmet or hood, serves to protect the user's respiratory system against chemicals listed in the filter label, especially against solvents, cyclohexane, hydrogen cyanide, hydrogen sulfide, chlorine, hydrogen chloride, nitrogen dioxide, sarin, phosgene, ozone and the like. Other chemical substances and their compounds are listed on the website of SIGMA Výzkumný a vývojový ústav, s.r.o (Research and development institute).

ATTENTION!

The filter is not suitable for use with half masks due to the weight exceeding 300 g.

The filter must not be used:

- against carbon monoxide (CO), carbon dioxide (CO₂), nitric oxide (NO) and nitrous oxide (N₂O)
- in an explosive atmosphere,
- in an environment with an oxygen volume (O₂) less than 17%



INSTRUCTIONS FOR USE

OF – 02 CBRN, OF-02 CBRN+ COMBINATION FILTERS

The anti-gas part of the filter complies with class 2 according to EN 14387 - concentration of test gas (pollutants) up to 0.5% of volume in air.

ATTENTION!

The filter must not be used at higher concentrations of pollutants.

The particulate part of the filter complies with class 3 according to EN 143

ATTENTION!

The real time of use of the filter cannot be determined in advance due to a number of factors that affect it. These include, in particular, the type and concentration of pollutants, humidity, temperature, flow and pulmonary ventilation of the user (working intensity).

PRINCIPLES FOR USING THE FILTER

1. The user should know the type of pollutants and their concentration which the filter intends to protect against.
2. Visually inspect the filter before using it. The filter must not be mechanically damaged.
3. Before opening the protective cover of the filter, check that the thread marking corresponds to the thread on the mask to which it is to be attached.
4. After opening the protective cover and before using the filter, remove the thread cover and the inlet to the filter.
5. Screw the filter into the mask and, after fitting it, check the tightness of the threaded connection by clogging the filter inlet with your hands. When inhaling, the mask must not be sucked in.
6. The filter can be used in the temperature range from - 30 °C to + 70 °C.

ATTENTION!

If the user detects an increase in respiratory resistance during use, the filter must be replaced.

If the user smells a change in air quality, the filter must be replaced immediately.

The odourless gas filter must always be replaced after each use.

MAINTENANCE AND REUSE OF THE FILTER

If the filter is used only against particles, the filter can be used repeatedly. In this case, close the filter with caps after use to prevent polluting or contamination of the surroundings. Thoroughly clean the filter or disinfect the surface of the filter, put it in its original packaging and store it in a safe place.

STORAGE

The filter must be stored under the prescribed conditions at a temperature from -10 °C to + 50 °C and a relative humidity of 0–95 % RH. The manufacturer guarantees the full functional performance of the filter in undamaged packaging and in compliance with the storage conditions until the date stated on the filter label.

ATTENTION!

Improper storage and/or broken protective packaging may reduce the protective capacity or cause irreversible damage to the filter.

DISPOSAL

Waste generated before and after the use of protective filters or after the end of product life must be disposed of in a manner as environmentally friendly as possible, recycled to the largest possible extent and disposal must be in accordance with the requirements of the legislation - EN ISO 14001:2016 Environmental management or legislation and the legislation of the user country.



The EU certificate of type examination No. 1024 / E-010/2019 was issued by Výzkumný ústav bezpečnosti práce (Research Institute of Occupational Safety), vvi, Jeruzalémská 1283/9, 110 00 Prague 1. Declaration of conformity at www.sigma-vvu.cz.

SIGMA Výzkumný a vývojový ústav, s.r.o. (Research and Development Institute)
Jana Sigmunda 313 | 783 49 LUTÍN | Czech Republic
Phone: +420 585 652 440 | E-mail: vvu@sigma.cz

Issued 2023/01
In case of any ambiguities or questions
contact the filter manufacturer or supplier.